

IN THE SPECIFICATION

Please replace the paragraphs on page 3, lines 5 - 15 of the application with the following amended paragraphs:

Figure 1 ~~depicts the perspective view of the preferred embodiments~~ is an exploded view of the parts of a guide rail assembly in accordance with the present invention.

Figure 2 ~~illustrates the side view of the drawer installed with the embodiments of the present invention, in a pulled-out state~~ shows a sectional view of a drawer having a guide rail assembly of Figure 1.

Figure 3 ~~illustrates the cross-sectional view~~ shows a side view of a ~~the~~ drawer installed with the embodiments of the present invention having a guide rail assembly of Figure 1, in a pulled-out state.

Figure 4 ~~illustrates another~~ is a perspective view of ~~the~~ a fully assembled guide rail in accordance with the preferred embodiments of the present invention assembly of Figure 1.

Please replace the paragraph on page 5, line 11 with the following amended paragraph:

Still referring to Figure 1, the outer pull out channel is as well in the form of an open C-section, in which the width of the said outer pull out channel 50 is substantially configured to receive the stabilizer ~~[[40]]~~ 10 and capable to slide therein. At the rear edge of the upper surface of the outer pull out channel 50 is provided with an inverted

L-shaped extension which functions as a back stopper 35, whereby this back stopper holds the drawer when it is pulled out. According to the present invention, the top surface of the outer pull out channel is preferably mounted to the bottom surface of the drawer to as well provide support and guided movement of the drawer.